



PRODUCT YOU CAN TRUST

# OPEN WEB FLOOR JOIST CONNECTORS

**UH**  
Universal Hanger

Designed for use in any joist to joist, joist to trimmer or joist to steel application.

**HUH**  
Heavy Universal Hanger

Designed for use in higher load joist to joist, joist to trimmer or joist to steel application.

**MHE**  
Multi Hanger (External Flange)

Designed to support timber to timber connections in situations of medium to high loading.

**FTHI**  
Flexible Timber Hanger

Designed to support joists in a top fix only application for high load situations. Options available for skewed, offset, dropped and straddle connections.

**VS**  
Variable Skewed Timber Hanger

Supports joists up to 97mm wide from solid timber members in skewed applications between 30° and 90°.

**MHI/MHIC**  
Multi Hanger (Internal Flange)

Internal flange option allows for multifunctional use when supporting timber to timber connections in medium to high load situations.

**UZ CLIP**  
Noggin Support

A multifunctional connector for supporting solid timber noggins.

**OW-CLIP**  
Multiple Joist Connector

Enables connection of 2 ply joists allowing them to act as a single unit.

**JHI**  
Masonry Joist Hanger

Traditional timber to masonry hanger range.

**SB-JHIR**  
Safe Build Masonry Joist Hanger

Provides a safe working platform with no need for masonry above.

**NEW HANGER**

**RB-JHI**  
Rapid Build Masonry Joist Hanger

Combines the standard JHI hanger with a reinforced top plate to achieve a safe working load without the need for masonry above.

**FMHI**  
Flexible Masonry Hanger

Supports joists from masonry walls in high load situations with 675mm masonry above.

**M-STD/M-RTN**  
Very High Load Masonry Hanger

Supports joists from masonry walls in very high load situations. Return options available to keep hanger tight to masonry wall.

**VSM**  
Variable Skew Masonry Hanger

Offers superior performance over traditional joist hangers. The unique design provides a variable skewed angle of between 30° and 90°.

**PFS**  
Pre Formed Strap

Typically used for lateral restraint in floor applications, exceeding performance of traditional 30 x 5mm strap.

**PST/PSB/PSC**  
Pre Formed Strap

Part of the parallel strap range, these provide required parallel restraint to blockwork for joist hangers and build-in details where required.

**RA**  
Restraint Angle Hanger

Timber to masonry hanger requiring no masonry above to perform to full capacity.

**HRAD**  
Heavy Restraint Angle Double Hanger

Timber to masonry hanger requiring no masonry above to perform to their full capacity for double joists and high load situations.

**RADS**  
Restraint Angle Double Skewed Hanger

Timber to masonry hanger requiring no masonry above to perform to their full capacity for skewed applications between 30° and 87.5°.

**DOWNLOAD CULLEN APP**

Download on the App Store

GET IT ON Google play

**PPN35Ci**  
Cordless Positive Placement Nailer

Makes light work of driving ETA approved, CE compliant hardened twist nails through hangers, connector plates and strapping - four times faster than a hammer.

**NAIL PACK**  
Square Twist Hardened Nails

Positive placement nails, for use with Paslode PPN35Ci.

Shank Type:	Square Twist Hardened
Shank Diameter:	3.4mm
Length:	35mm
Head Diameter:	7.0mm
Average Profile Diameter:	3.7mm
Finish:	12µm Electro Galv

**LOOSE NAILS**  
3.4 x 35mm Electro Galvanised Square Twist Nails

Connectors have been tested with these nails.

Shank Diameter:	3.4mm
Length:	35mm
Head Diameter:	8.0mm
Average Profile Diameter:	3.7mm
Finish:	12µm Electro Galv

**PSTS**  
Structural Timber Screws

Requires no pre-drilling, quick and easy to install.

Outer Thread Shank Diameter:	6.5mm	8.0mm
Plain Shank Diameter:	4.8mm	5.85mm
Length:	35 - 250mm	65 - 135mm
Head Diameter:	11.5mm	16mm
Finish:	5µm Electro Galv	5µm Electro Galv

